

M-1073H

Dual 7-inch FHD Rack LCD Monitor



■ Introductions

- ◆ Dual 7" non-glaring LCD, 1920×1200
- ◆ 19-inch 3U rack mount, ±30° rotatable
- ◆ 2K/3G/HD/SD-SDI input & loop output
- ◆ HDMI 2.0 (4K60p) input & loop output
- ◆ 16-ch embedded audio meters with alert
- ◆ Select any 2 audio channels to output
- ◆ 9 steps quick zoom-in and mapping
- ◆ Focus assist with precision adjustment
- ◆ Build-in multi-camera logs to Rec.709
- ◆ User 3DLUT cube file import by USB
- ◆ On-screen TALLY display and GPI
- ◆ Zebra stripes, False color, R/G/B/Mono
- ◆ H/V delay, AFD, Timecode display
- ◆ Marker 4:3, 13:9, 14:9, 15:9, 1.85:1, 2.35:1
- ◆ USB firmware upgrade

■ Specification

LCD Performance		
Size	7 inches×2	
Display area	151.2×94.5mm	
Resolution	1920×1200	
Aspect ratio	16:9 (4:3 adjustable)	
Brightness	400cd/m ²	
Contrast	1000:1	
Color	16.77 million colors	
Viewing angle	Horizontal: 160°; Vertical: 160°	
Input/output (Each LCD)		
Input	2K/3G/HD/SD-SDI input	2K/3G/HD/SD-SDI input
	HDMI 2.0 input	HDMI 2.0 input
	Firmware upgrade	Firmware upgrade
	GPI (Tally) input	GPI (Tally) input
Output	BNC ×1	2K/3G/HD/SD-SDI loop output
	HDMI ×1	HDMI 2.0 loop output
	3.5mm ×1	SDI, HDMI embedded audio output
Video Format		
SDI	SMPTE-2048-2	2048×1080p (23.98 / 24 / 25 / 29.97 / 30 / 50 / 59.94 / 60)
		2048×1080i (50 / 59.94 / 60)
	SMPTE-425M	1080p (60 / 59.94 / 50)
		1080i (60 / 59.94 / 50)
	SMPTE-274M	1080p (30 / 29.97 / 25 / 24 / 23.98)
		1080psf (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M	720p (60 / 59.94 / 50)
SMPTE-125M	480i (59.94)	
ITU-R BT.656	576i (50)	
HDMI	4096×2160p (60 / 50 / 30 / 25 / 24)	
	3840×2160p (60 / 50 / 30 / 25 / 24)	
	1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
	1080i (60 / 59.94 / 50)	
	720p (60 / 59.94 / 50)	
	480i / 576i / 480p / 576p	
General		
Input voltage	DC 6.5V-36V	
Power consumption	18-26W	
Working temperature	-10°C~+50°C	
Working humidity	10%~90%	
Storage temperature	-15°C~+60°C	
Storage humidity	10%~90%	
Dimensions	484×130×82mm	
Net weight (main body)	2.4kg	